



# TECHNICAL COMPARISON - SILVER

Model		Replacement		Replacement
N. America (NEMA P-15)	S1Q-PA	S2Q-PA	S12Q-PA	VH410
EU CEE (CEE 7-7)	S1Q-PA/2	S2Q-PA/2	S12Q-PA/2	VH410/2
DINSINFECTON FLOW RATES				
30mJ/cm2	2 GPM (7 lpm)	3 GPM (11 lpm)	15 GPM (57 lpm)	18 GPM (70 lpm)
SPECIFICATIONS				
Dimensions inch (cm)	15.5" x 2 1/2" (39.4 cm x 6.5 cm)	17" x 2 1/2" (43.6 cm x 6.5 cm)	37 1/2" x 3 1/2" (95.3 cm x 8.9 cm)	23 1/2" x 3 1/2" (59.6 cm x 8.9 cm)
Shipping Weight lbs (kg)	6lbs (2.7kg)	7 lbs (3.2 kg)	13 lbs (5.9 kg)	17 lbs (7.7 kg)
Connection Size	1/4" MNPT	1/2" MNPT	3/4"- 1" MNPT COMBO	3/4"- 1" MNPT COMBO
Power Consumption	19W	22W	48W	60W

Model		Replacement			Replacement
N. America (NEMA P-15)	SV12Q-PA	660039-R (D4-V)	SSMV-37	SSMV-39	660042-R (D4-V+)
DINSINFECTON FLOW RATES					
16mJ/cm2 (NSF-B)	9.2 GPM (35 lpm)	8.9 GPM (34 lpm)	7 GPM (26 lpm)	9.2 GPM (35 lpm)	8.9 GPM (34 lpm)
SPECIFICATIONS					
Dimensions inch (cm)	37 1/2" x 3 1/2" (95.3 cm x 8.9 cm)	20 1/2" x 4" (52 cm x 10 cm)	35 1/2" x 2 1/2" (90.4 cm x 6.5 cm)	37 1/2" x 3 1/2" (95.3 cm x 8.9 cm)	20 1/2" x 4" (52 cm x 10 cm)
Shipping Weight lbs (kg)	13 lbs (5.9 kg)	10 lbs (4.5 kg)	11 lbs (5.0 kg)	13 lbs (5.9 kg)	10 lbs (4.5 kg)
Connection Size	3/4"- 1" MNPT COMBO	3/4" MNPT	3/4" MNPT	3/4"- 1" MNPT COMBO	3/4" MNPT
Power Consumption	48W	50W	46W	48W	50W

Model			Replacement
N. America (NEMA P-15)	SSM-37	SSM-39	VH410M
EU CEE (CEE 7-7)	SSM-37/2	SSM-39/2	VH410M/2
DINSINFECTON FLOW RATES			
30mJ/cm2	10 GPM (38 lpm)	15 GPM (57 lpm)	18 GPM (70 lpm)
SPECIFICATIONS			
Dimensions inch (cm)	35 1/2" x 2 1/2" (90.4 cm x 6.5 cm)	37 1/2" x 3 1/2" (95.3 cm x 8.9 cm)	23 1/2" x 3 1/2" (59.6 cm x 8.9 cm)
Shipping Weight lbs (kg)	11 lbs (5.0 kg)	13 lbs (5.9 kg)	17 lbs (7.7 kg)
Connection Size	3/4" MNPT	3/4"- 1" MNPT COMBO	3/4" - 1" COMBO NPT
Power Consumption	46W	48W	60W

Model		Replacement			Replacement
N. America (NEMA P-15)	S1Q-DWS	VT1-DWS	S2Q-DWS	S5Q-DWS	VT4-DWS
EU CEE (CEE 7-7)	S1Q-DWS/2	VT1-DWS/2	S2Q-DWS/2	S5Q-DWS/2	VT4-DWS/2
DINSINFECTON FLOW RATES					
30mJ/cm2	2 GPM (7 lpm)	1 GPM (4 lpm)	3 GPM (11 lpm)	6 GPM (23 lpm)	3.5 GPM (13 lpm)
SPECIFICATIONS					
Dimensions inch (cm)	14" x 16" x 6" (35.5 cm x 40.6 cm x 15 cm)	15" x 17" x 6" (38 cm x 43 cm x 15 cm)	15.5" x 16" x 6" (39 cm x 40.6 cm x 15 cm)	20.5" x 28" x 6" (52 cm x 71 cm x 15 cm)	19" x 27 1/2" x 6" (48 cm x 70 cm x 15 cm)
Shipping Weight lbs (kg)	14 lbs (6.5 kg)	14 lbs (6.4 kg)	16 lbs (7.3 kg)	20 lbs (9.1 kg)	20 lbs (9.1 kg)
Connection Size	1/4" MNPT	3/8"-1/2" COMBO NPT	1/2" MNPT	3/4" MNPT	1/2" MNPT
Power Consumption	19W	13W	22W	30W	20W

Model		Replacement
N. America (NEMA P-15)	S1Q-P/12VDC	S2Q-P/12VDC
DINSINFECTON FLOW RATES		
30mJ/cm2	2 GPM (7 lpm)	2 GPM (8 lpm)
SPECIFICATIONS		
Dimensions inch (cm)	15.5" x 2 1/2" (39.4 cm x 6.5 cm)	17" x 2 1/2" (43.6 cm x 6.4 cm)
Shipping Weight lbs (kg)	6lbs (2.7kg)	7 lbs (3.2 kg)
Connection Size	1/4" MNPT	1/2" MNPT
Power Consumption	15W	17W

